

HYBRID DIGITAL VIDEO RECORDER

YDS-1651GR

Feature

- Compatible Analogue (AHD/TVI/CVBS/TVI) & IP camera
- Recording up to 5MP Analogue and 4MP IP camera
- Display channel up to 25CH
- Intelligent function
- P2P optional
- OSD setting over coaxial (UTC)
- Mac Safari browser support
- Support iOS & Android mobile surveillance function
- Remote Controller enclosed



Specification

General	Model	YDS-1651GR
	Max. Channels	Analogue cam 16CH / IP cam 8CH
	Video Input	Up to 24CH (Analogue video + IP video)
	Input Resolution	Analogue Camera: 5MP (20fps) / 4MP/3MP(30fps) / 1080P / 720P / 960H / D1 IP Cam: 4MP / 3MP / 1080P / 720P
	Output	1 x HDMI / 1 x VGA
Function	UTC	Yes
	Audio Input/Output	4 x RCA / 1 x RCA
	Recording Mode	Manual / Continuous / Motion detection
	Recording Resolution	Analogue Camera: 5MP@10fps(each ch) 4MP@15fps(each ch) 3MP@20fps(each ch) 1080P@PAL:25fps(each ch) / NTSC:30fps(each ch) 720P@PAL:25fps(each ch) / NTSC:30fps(each ch) 960H / D1@PAL:25fps(each ch) / NTSC:30ps(each ch) IP Cam: PAL: 25fps(each ch) / NTSC: 30fps(each ch)
	Display Mode	1/4/6/8/9/10/13/14/16/17/19/22/25/S.E.Q.
	Playback	16CH simultaneous
	Playback Search	Smart / Time / Event
Storage	Internal Storage	2 x SATA ports (Up to 12TB)
	Backup	Local USB & Remote by web browser
Network	Network Protocol	Static / DHCP / DDNS
	Max. Input Bandwidth	64 Mbps
	Max. Output Bandwidth	128 Mbps
	Network Port	10/100/1000Mbps, 1 x RJ45
Others	USB	1 x USB3.0, 2 x USB2.0
	Alarm	Option
	RS485	D+, D-
	Power	DC 12V / 5A
	Dimension (WxHxD)	378(W) x 50(H) x 340(D) mm
	Operation Temp.	-10°C ~ +55°C