

4G/LTE IP OUTDOOR CAMERA

YUC-K7CA6ML (4.2X)



Feature

- 3G 4G/LTE Camera
- Support 2.5" SSD and SD card for recording
- H.265 compression saves bandwidth up to 50%
- 2MP (1920x1080) 60fps real time & True WDR
- Starlight performance
- Built-in 4.2X motorized zoom lens 2.8-12mm
- Built-in GPS module
- ROI (Region of Interest) & smart stream function
- Smart IR to 40 Meter
- Remote motion storage to Google Drive and Dropbox
- IP66
- Mobile view support (push video)
- P2P (peer-to-peer) easy installation
- PoE support
- Support power by solar panel
- ONVIF compliant



Save Until 50% of HDD Space



Support power by solar panel



Solution for isolated places: remote cabins, farms, boats, rental properties, construction sites, campsites, warehouses

Specification

YUC-K7CA6ML (4.2X)

Server	Compression	H.265 / H.264 / MJPEG, 4 Streams
	Resolution	1920x1080@60fps, 1920x1080@30fps, 1280x720@30fps,640x480@30fps, 320x240@30fps
	Traffic Control	32K ~ 8Mbps
	Max. Frame Rate	(60fps)1920x1080
	Safety	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP
	Protocols	IPv6, IPv4, HTTP, HTTPS, SNMP, SSL, TLS, DNS, ICMP, IGMP, ARP, SNTP, QoS/DSCP, IEEE 802.1X, RTSP/RTP/RTCP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA, Bonjour, Google Drive, Dropbox, ONVIF Profile S, RTMP
	Number of User	Max. 10 connections
	Alerting	SMTP / FTP / Samba / SD card / IO / Google Drive / Dropbox
	Pre / Post Alarm	Pre(0,1,2,3,4,5) / Post(0,1,2,3,4,5,10)seconds
	Release for Alarm	Motion Detection / IO / Tampering Detection / Sound Detection
Network Camera	Sensor	1/2.8" Sony STARVIS CMOS sensor IMX 307
	Optical Lens	Motorized lens 2.8-12mm / optical 4.2X zoom in / F1.4
	View Angle	35~95°(H), 19~50°(V)
	WDR	Ture WDR 130dB
	AGC	8X ~ 128X
	Shutter Time	Outdoor / Indoor / 1/30, 1/50, 1/60, 1/100, 1/125, 1/250, 1/500, 1/1000, 1/5000, 1/10000
	Min Illum	0.005 Lux (Color), 0.001 Lux (B/W)
	IR LED / Range	6pcs High Power LED / 40M
	Day / Night	Light sensor mode / Color mode(Day) / B/W mode(Night) / Times mode / Synchronize with DI input
	Intelligent Feature	ROI / Smart Stream / IVA: Double Trigger: Motion + IO / Tampering Detection / Sound Detection / Lens Distortion Correction (LDC) / Anti Fog / True WDR / Corridor Mode / Privacy Mask / 3D-De Noise / Smart IR / Cloud Backup / ANR (Automatic Network Replenishment) / Push Video Notification / P2P
GNSS	GPS	GPS/GLONASS/BeiDou/Galileo/QZSS
LTE Bands	Europe Module	LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8
	America Module	LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71 WCDMA: B2/B4/B5
	Japan Module	LTE FDD: B1/B3/B8/B18/B19/B26 LTE TDD: B41 WCDMA: B1/B6/B8/B19
	SIM Card Slot	External micro sim card slot
Audio	Audio Compression	G.711(64Kbps) / G.726(32Kbps) / G.726(24Kbps)
	Adjust Volume	Mic-in / Audio-out web adjustable
	Audio In	3.5mm stereo jack, support 2 way
	Audio Out	3.5mm stereo jack, support 2 way

Terminal	Network Interface	Ethernet (10Base-T/100Base-Tx) / PoE
	Video Interface	BNC, Composite Video (NTSC / PAL)
	External Port	DI x 1 / DO x 1 / Default x 1
	SSD	- 2.5 inch SATA port x 1 support up to 1TB - Recording for schedule, Motion detection, IP check, Network wire break down, DI - Recording management
	SD Card	- Micro SD Card Slot support up to 256G - Recording for schedule, Motion detection, IP check, Network wire break down, DI - Recording management
General	Operation Voltage	DC 12V Max: 5.5W / PoE Max: 7.0W
	Dimen./Weight	157mm(W) x 131mm (H) x 460mm(L) / 2750g
	Operation Temp.	-20°C ~ +60°C
	Enclosure Certificate	IP66